

REFERENCE GUIDE

HOW TO ORDER TABLE SKIRTING

1. SELECT A FABRIC/PATTERN

Choose from the vast selection of fabrics and patterns featured in this catalog: DuraLast™ 100% Polyester Weaves, SoftWeave™ Spun Filament Polyester Weaves, TruFinish™ 100% Polyester Weaves

NOTE: Be sure to include item number of each fabric and/or pattern selected.

2. SELECT A COLOR

Set the mood you desire with color. Soft pastels create a quiet, relaxing setting; bold jewel tones generate excitement. Table skirting can be color coordinated to match your existing decor or provide drama by using contrast colors and prints. DuraLast™ and SoftWeave™ are dyed to match, letting you mix and match fabrics for added texture.

NOTE: Be sure to include color number of each item selected.

3. SELECT A PLEAT STYLE

Our selection includes standard pleat styles: Shirred Pleat (S), Box Pleat (B), and Accordion Pleat (A) and optional pleat styles: Continuous Accordion (CA) and Continuous Box (CB).



Shirred Pleat



Box Pleat



Accordion Pleat








Continuous Box Pleat



Continuous Accordion Pleat

4. DETERMINE THE SIZE YOU NEED

Marko® By Carlisle recommends a standard 29" (74cm) drop for a 30" (76cm) high table. To determine the appropriate skirt length, measure the perimeter of the table and order skirting by the running foot. See examples below:

Buffet Table To skirt all four sides, simply measure and add all four sides of the table.	 Skirting on 4 sides	30" x 72" (76cm x 183cm) 17 Feet (5.18m)	36" x 72" (91cm x 183cm) 18 Feet (5.48m)	30" x 96" (76cm x 244cm) 21 Feet (6.4m)	36" x 96" (91cm x 244cm) 22 Feet (6.7m)
Head Table To skirt three sides, simply measure and add all three sides of the table.	 Skirting on 3 sides	30" x 72" (76cm x 183cm) 11 Feet (3.4m)	36" x 72" (91cm x 183cm) 12 Feet (3.66m)	30" x 96" (76cm x 244cm) 13 Feet (3.96m)	36" x 96" (91cm x 244cm) 14 Feet (4.27m)
Head Table with Return Measure the three sides you want skirted and add two 6" (15cm) returns for the non-visible side.	 Skirting on 3 sides with 6" (15cm) returns	30" x 72" (76cm x 183cm) 12 Feet (3.66m)	36" x 72" (91cm x 183cm) 13 Feet (3.96m)	30" x 96" (76cm x 244cm) 14 Feet (4.27m)	36" x 96" (91cm x 244cm) 15 Feet (4.57m)
Two Head Tables with Return Measure the three sides of the two head tables together you want skirted and add two 6" (15cm) returns for the non-visible side.	 Skirting 2 tables together on 3 sides with 6" (15cm) returns	2 tables: 30" x 72" (76cm x 183cm) 18 Feet (5.49m)	2 tables: 36" x 72" (91cm x 183cm) 19 Feet (5.79m)	2 tables: 30" x 96" (76cm x 244cm) 22 Feet (6.71m)	2 tables: 36" x 96" (91cm x 244cm) 23 Feet (7.01m)
Round Table Measure the perimeter of the table.	 Skirting all around table	48" Diameter (122cm) 13 Feet (3.96m)	60" Diameter (152cm) 16 Feet (4.88m)	66" Diameter (168cm) 17 1/2 Feet (5.33m)	72" Diameter (183cm) 19 Feet (5.79m)

NOTE: If your requirements differ, please specify exact sizes on your order.

5. SELECT A SKIRT HEADER

Table skirting is available with either standard slotted webbing or a velcro header. Since clips are attached directly to the webbing, standard slotted webbing provides a snug fit around any corner or table shape, i.e., serpentine tables. For quick set ups and tear downs, consider the velcro header.

REFERENCE GUIDE

6. SELECT AN ATTACHMENT SYSTEM

Marko® By Carlisle has five different attachment systems to choose from. The thickness of the table edge and type of header will help determine which attachment system to use. Our selection of clear-top, Spring-On™, stainless steel, unbreakable clips accommodates standard slotted webbing and velcro headers, fitting table edges 3/8" to 2-1/2" (10mm to 64mm). The plastic velcro clips have openings that range from 3/8" to 5" (10mm to 127mm) and work only with velcro headers. Velcro Stripping and Velcro Patches can accommodate any size table edge, but only work with velcro headers. T-pins can accommodate any table edge size and header. For additional information refer to our clip sizing guide on page 43.


CLEAR-TOP SPRING-ON™, STAINLESS STEEL, UNBREAKABLE CLIPS



Standard Slotted Webbing (photo A):
5112MP - for table edge 3/8" to 1-1/4" (10mm to 32mm)
5117MP - for table edge 1-1/4" to 2-1/4" (38mm to 57mm)

velcro header (photo B):
5118MP - for table edge 3/8" to 1-1/4" (10mm to 32mm)
5120MP - for table edge 1-1/4" to 2-1/4" (38mm to 57mm)

NOTE: All clips above are 3/4" (19mm) wide; 550PC can be interchanged with 5118MP clips.



Shown: 5112MP with Standard Slotted Webbing

Shown: 5118MP with velcro Header

PLASTIC VELCRO CLIPS



550PC

- fits table edges 3/8" to 1" (10mm to 25mm)



555PC (OVERLAP/VALANCE CLIP)

- flat clip is designed to hold excess skirting in place
- 1/2" (13mm) opening



5200PC

- fits table edges 3/8" to 3/4" (10mm to 19mm)

5CCLIP (for bull-nosed table edges)

- 3/4" to 1-1/2" (19mm to 38mm) opening

new!

5LCLIP

- fits extra large table edges up to 5" (127cm)

ADDITIONAL ATTACHMENT SYSTEMS



521C VELCRO STRIPPING

- use with velcro header only
- 5/8" (16mm) wide



522C VELCRO PATCHES

- use with velcro header only
- 5/8" (16mm) wide x 1" (25mm) long



5TPINS

- use with standard webbing or velcro header
- 1-3/4" (45mm) long

7. INSTALL TABLE SKIRTING

Standard Slotted Webbing Clips (5112MP, 5117MP): First slip clips into the slotted webbing every 7" (18cm) [every third slot]; then attach the clips to table edge, slipping them over the table topper

Velcro Clips (5118MP, 5120MP, 550PC, 5200PC, 5CCLIP), 521C Velcro Stripping, 522C Velcro Patches: Attach velcro clips, stripping, or patches to the table edge first; then press the velcro header onto the clips, stripping, or patches

5TPINS: Pin skirt header to the table topper

8. INSTALL OVERLAP/VALANCE

555PC Velcro Clip: Slip the clip between the skirting already installed on the table and the table edge; then press the velcro header onto the velcro on the clip